



l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
3	1458442 3					
4	1458442 4	14584425 4	1458443 4			
5	1458442 5	14584425 5	1458443 5	1458444 5		
6	1458442 6	14584425 6	1458443 6	1458444 6	1458445 6	
8	1458442 8	14584425 8	1458443 8	1458444 8	1458445 8	1458446 8
10	1458442 10	14584425 10	1458443 10	1458444 10	1458445 10	1458446 10
12	1458442 12	14584425 12	1458443 12	1458444 12	1458445 12	1458446 12
14	1458442 14	14584425 14	1458443 14	1458444 14	1458445 14	1458446 14
16	1458442 16	14584425 16	1458443 16	1458444 16	1458445 16	1458446 16
18	1458442 18	14584425 18	1458443 18	1458444 18	1458445 18	1458446 18
20	1458442 20	14584425 20	1458443 20	1458444 20	1458445 20	1458446 20
22			1458443 22	1458444 22	1458445 22	1458446 22
25	1458442 25	14584425 25	1458443 25	1458444 25	1458445 25	1458446 25
28			1458443 28	1458444 28	1458445 28	1458446 28
30	1458442 30	14584425 30	1458443 30	1458444 30	1458445 30	1458446 30
35			1458443 35	1458444 35	1458445 35	1458446 35
40			1458443 40	1458444 40	1458445 40	1458446 40
45			1458443 45	1458444 45	1458445 45	1458446 45
50			1458443 50	1458444 50	1458445 50	1458446 50
55				1458444 55	1458445 55	1458446 55
60				1458444 60	1458445 60	1458446 60
65				1458444 65	1458445 65	1458446 65
70				1458444 70	1458445 70	1458446 70
75				1458444 75	1458445 75	1458446 75
80				1458444 80	1458445 80	1458446 80
85					1458445 85	1458446 85
90					1458445 90	1458446 90
95					1458445 95	1458446 95
100					1458445 100	1458446 100
Ø	1000	1000	500	500	500 >= 45 200	500 >= 25 200
dk	3,8	4,7	5,5	8,4	9,3	11,3
k	1,2	1,5	1,65	2,7	2,7	3,3
Antrieb	TX6	TX8	TX10	TX20	TX25	TX30

ISO 14584 A4
 Linsensenkschrauben mit Innensechsrund

ISO 14584 A4
 Raised countersunk head screws with six lobe drive

ISO 14584
 A4
 Alternative Norm
 ehemals DIN 966

l/mm	Art. Nr. / Item no.
3	
4	
5	
6	
8	
10	
12	1458448 12
14	
16	1458448 16
18	
20	1458448 20
22	
25	1458448 25
28	
30	1458448 30
35	1458448 35
40	1458448 40
45	1458448 45
50	1458448 50
55	
60	1458448 60
65	
70	1458448 70
75	
80	1458448 80
85	
90	
95	
100	
⌀	200
	>= 60
	100
dk	15,8
k	4,65
Antrieb	TX45

